

DR-U16S Specifications

General	
Supported Disc Formats	CD-ROM, CD-DA, CD-R, CD-RW, CD-ROM XA
Media Diameter	120 mm / 80 mm
Media Handling	Slot-In loading mechanism
Interface	SCSI-2 (SCAM)
Data Transfer Rate (Sustained)	2160 - 5400 KB/s (14-36X)
Data Transfer Rate (Burst)	10 MB/s
Random Average Seek Time	60 ms
Random Average Access Time	70 ms
Data Buffer Capacity	128 KB
Data Block Size	2048 / 512 Bytes
Disc Startup Time	max. 10 seconds
Disc Spin Down Time	max. 7 seconds
Mean Time Between Failure	100,000 Power On Hours / 20% Duty
Headphone Connector	Stereo Mini-Jack
Output Level	0.7 ± 0.1 Vrms (Line Out)
Frequency Response	17 ~ 20000 Hz (± 2 dB)
Total Harmonic Distortion	0.3% or less
Physical Characteristics	
Dimensions (W x H x D)	148 x 42.3 x 207.5 mm
Operating Voltage	+ 12V, + 5V
Net Weight	0.99 kg
Environmental Conditions	
Operating Temperature	5 °C to 45 °C
Operating Humidity (non-condensing)	5 to 85% RH
Storage Temperature	-20 °C to 60 °C
Storage Humidity (non-condensing)	5 to 90% RH